


FIRST AID FIRE HOSE

FRH Series

Copely



Fully compliant with EN694, the renowned First Aid Fire Hose combines the benefits of both rubber and PVC to produce a superior quality, reliable product that is today a European market leader in the emergency hose market.

Key Features:

- Exceeds the requirements of EN694.
- Good flexibility and durability.
- Balanced and lighter in weight for easier handling.
- Outstanding UV / Ozone resistance making it suitable for indoor and outdoor use.
- Type A construction consisting of a seamless rubber/PVC lining; a textile reinforcement with an elastomeric rubber/plastics cover.
- Cadmium and silicone free.
- Resistant to a wide range of chemicals.
- 3:1 safety factor.
- RoHS 3 compliant.

Sizes:

Available in 30 m coils
19 mm and 25 mm ID

Custom sizes available on request subject to minimum order quantity

Colours:

Red outer / black inner



1. DEHP free PVC liner
2. Polyester fiber reinforcement
3. DEHP free PVC outer



Applications:

- Fixed fire reel hoses in buildings –exterior or interior.

Product Ref	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure	Weight per Metre	Bend Radius
FHR19	19 mm	26 mm	12 Bar	42 Bar	0.360 Kg	135 mm
FHR25	25 mm	34 mm	12 Bar	42 Bar	0.632 Kg	210 mm