

# RUBBER AIR HOSE

## RAH Series

Copely



A black, weather and ozone resistant compressed air hose suitable for general workshop use and compressors.

Manufactured from NBR / SBR synthetic rubber with high tensile synthetic textile reinforcement. Medium duty service for air and pneumatic tools including workshops with compressors, mines, quarries and construction.

### Key Features:

- Abrasion, ozone and weather resistant.
- Smooth rubber NBR / SBR construction.
- In accordance with EN ISO 2398.
- Wide temperature range 40 °C to +90 °C.
- Safety factor 3:1.

### Sizes:

Available in 25 m coils

### Colours:

Black



1. NBR/SBR Rubber inner
2. Polyester fibre reinforcement
3. NBR/SBR Rubber outer



### Applications:

- Construction
- General workshop use
- Compressors
- Mines
- Quarries



Product Ref	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure	Weight per Metre	Bend Radius (Approx.)
RAH06	6 mm	12 mm	20 Bar	60 Bar	0.18 Kg	60 mm
RAH08	8 mm	15 mm	20 Bar	60 Bar	0.23 Kg	80 mm
RAH10	10 mm	17 mm	20 Bar	60 Bar	0.29 Kg	100 mm
RAH13	13 mm	21 mm	20 Bar	60 Bar	0.43 Kg	130 mm
RAH16	16 mm	25 mm	20 Bar	60 Bar	0.60 Kg	160 mm
RAH19	19 mm	29 mm	20 Bar	60 Bar	0.70 Kg	190 mm
RAH25	25 mm	36 mm	20 Bar	60 Bar	1 Kg	250 mm